

INDEX

AA	Age Allowance	Appendix 6
AMG	Asymmetric Spinnaker Mid Girth	10.23
ASF	Asymmetric Spinnaker Foot	10.22
ASL	Asymmetric Spinnaker Luff (see also SLU & SLE)	10.21
BAL	Boom After Sheeting Limit	9.10.2
BALY	Boom After Sheeting Limit, Mizzen	9.19.2
BAS	Main Boom Above Sheerline	9.09
BASY	Mizzen Boom Above Sheerline	9.18
BCW	Base Crew Weight	8.11
BD	Boom Diameter, Main	9.11
BDY	Boom Diameter, Mizzen	9.20
BLRI	Ballast-Leeward Recovery Index	2.02.2
CANT	Cant Angle -- Canting Keel	Appendix 7, 2.d
CPW	Chainplate Width	9.13
CW	Crew Weight	9.11
DA	Dynamic Allowance	Appendix 6
DCW	Declared Crew Weight	8.12
DHK	Maximum Draft Including Keel	6.13
DHKA	Draft of Keel and Hull Adjusted	6.14
DSPM	Displacement in Measurement Trim	6.11
DSPS	Displacement in Sailing Trim	6.11
E	Foot of Mainsail	9.10.1
EB	Distance Between Masts	9.21
EDM	Effective Diameter Main Mast	10.49
EDMY	Effective Diameter Mizzen Mast	10.51
EHM	Effective Height of Main Mast	10.48
EHMY	Effective Height Mizzen Mast	10.5
EY	Foot of Mizzen	9.19.1
FSP	Forestay Perpendicular	10.14
GO	Forestay Outtrigger	9.06.3
GPH	General Purpose Handicap	Appendix 4, 4.a
GSA	Gauge Surface Area, Inclining Manometer	8.02
HB	Headboard of Mainsail	10.3
HBS	Spinnaker Headboard	10.19
HBY	Headboard of Mizzen	10.35

HMI	Hull Measurement Instrument	1.04
IG	Height of Genoa Hoist	9.06.1
IM	Foretriangle Height	10.43
ISP	Height of Spinnaker Halyard	9.06.2
IY	Height of Mizzen Mast	9.15
J	Base of Foretriangle	9.04
JL	Longest Luff of Jibs	10.15
JR	Jib Roach	10.13.5
L	Sailing Length	6.10
LIST	List Angle -- Moveable Ballast Yachts	Appendix 7, 1.e
LL	Luff Limit of Spinnaker	10.45.8
LOA	Length Overall	6.04
LP	Longest Perpendicular of Jibs, Rated	10.44
LPG	Longest Perpendicular of jibs	10.12
LPS	Limit of Positive Stability	2.02.1
MB	Maximum Beam (nominal)	6.05
MCG	Mast Vertical Center of Gravity	8.14.1
MDL1	Maximum Longitudinal Dimension of Main Mast	9.06.6
MDL1Y	Maximum Longitudinal Dimension of Mizzen Mast	9.16
MDL2	Longitudinal Dimension of Main Mast at Head	9.06.9
MDL2Y	Longitudinal Dimension of Mizzen Mast at Head	9.16
MDT1	Maximum Transverse Dimension of Main Mast	9.06.5
MDT1Y	Maximum Transverse Dimension of Mizzen Mast	9.16
MDT2	Transverse Dimension of Main Mast at Head	9.06.8
MDT2Y	Transverse Dimension of Mizzen Mast at Head	9.16
MGL	Mainsail Girth, Lower	10.32.1
MGLY	Mizzen Girth, Lower	10.37
MGM	Mainsail Girth, Mid	10.32.1
MGMY	Mizzen Girth, Mid	10.37
MGT	Mainsail Girth, Top	10.32.1
MGTY	Mizzen Girth, Top	10.37
MGU	Mainsail Girth, Upper	10.32.1
MGUY	Mizzen Girth, Upper	10.37
MSW	Mainsail Weight	10.33

MW	Mast Width	9.06.4
MWT	Mast Weight	8.14.1
P	Mainsail Hoist	9.07
PIPA	Propeller Installation Projected Area	2.04
PL	Pendulum Length, Inclining Manometer	8.02
PLM	Pendulum Length, Measured, Inclining Manometer	8.02
PY	Mizzen Hoist	9.17
RM	Righting Moment	8.07
RMC	Righting Moment Corrected	8.08
RM2	Righting Moment per Degree in Sailing Trim at 2 degrees heel	8.09
RM20	Ditto 20 Degrees Heel	8.10
RM40	Ditto 40 Degrees Heel	8.10
RM60	Ditto 60 Degrees Heel	8.10
RM90	Ditto 90 Degrees Heel	8.10
RSA	Reservoir Surface Area, Inclining Manometer	8.02
SF	Symmetric Spinnaker Foot Length	10.22
SFJ	Stem to forward end of J	9.04.1
SG	Specific Gravity, Flotation Measurement	5.02.1
--	Sheer Point	5.01.4, Appendix 3
--	Sheer Line	5.01.5
SL	Symmetric Spinnaker Luff/Leech Length	10.21
SLE	Asymmetric Spinnaker Leech	10.21.2(b)
SLU	Asymmetric Spinnaker Luff	10.21.2(a)
SMW	Symmetric Spinnaker Maximum Width	10.20
SPL	Spinnaker Pole Length	9.05.2
--	Stability Index	2.02.1
TH	Taper Hollow	10.49
TL	Tapered Length of Main Mast	9.06.7
TLY	Tapered Length of Mizzen Mast	9.16
TPS	Tack Point, Spinnaker	9.05.3
VPP	Velocity Prediction Program	1.02

WB	Weight of Boom	9.14.4
WBV	Water Ballast Volume	Appendix 7
WD	Weight Distance, Inclining Weights	8.03
WSS	Wetted Surface, Upright Sailing Trim	6.12
YSD	Mizzen Staysail Depth	10.40
YSF	Mizzen Staysail Foot	10.39
YSMG	Mizzen Staysail Mid Girth	10.4